

HOT SPOT[®] COLLECTION

STRIDE®





7' x 5'5" x 29"

FROG[®] In-Line Cartridge Ready

Dimensions

Water Care

HOT SPOT[®] COLLECTION STRIDE R








Stride spa shown with Alpine White shell and Almond cabinet.

Shell Colors







Cabinet Colors

Almond







Cover Colors

Stone

Seating Capacity	3 people	Control System	IQ 2020® 115 V / 20 amp,** 60 Hz (Includes G.F.C.I. protected power cord) or
Dimensions	7' x 5'5" x 29" / 2.13 m x 1.65 m x 0.74 m		115 V / 30 amp*** or 220 V / 50 amp,*** 60 Hz
Water Capacity	225 gallons / 850 liters	Lighting – Interior	6 multi-color LED points of light, dimmable
Weight	570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled*	Lighting – Exterior	4 multi-color LED points of light, dimmable
Jets (All with stainless steel trim)	20 total • 1 XL Directional Hydromassage jet	Heater	No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
,,	 1 XL Rotary Hydromassage jet 3 Directional Hydromassage jets 1 Rotary Hydromassage jet 14 Directional Precision[®] jets 	Energy Efficiency	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Jet Pump	Wavemaster [®] 6200; Two-speed,	Effective Filtration Area	30 sq. ft., top loading
	1.5 HP Continuous Duty, 3.2 HP Breakdown Torque	Vinyl Cover	3.5" to 2.5" tapered, 1.5 lb. density foam core
		Cover Lifter (Optional)	CoverCradle [®] , CoverCradle II, or UpRite [®]
Floor Drain		Steps (Optional)	Everwood® - Almond, Havana, and Storm
Water Care System	FROG® In-Line Cartridge Ready		Polymer - Ash

Actual colors and products may vary from print representation. See dealer to verify. *Includes water and 3 adults weighing 175 lbs. each. **Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. *** G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater. © 2020 Watkins Wellness • Rev. C