

# HOT SPOT® COLLECTION

# SX



FreshWater®  
Salt System  
Ready



FiberCor®  
High-Density Insulation



Moto-Massage®



*Shown with Alpine White Shell  
and Havana Cabinet.*



<b>People</b>	<b>Seating</b>	<b>Jets</b>	<b>Voltage</b>
3 Seats	Open	18 Jets	115 V or 230 V

**Size**  
6' x 6'5" x 33" | 183 cm x 196 cm x 84 cm

**Water Care**  
FreshWater® Salt System Ready

# HOT SPOT® COLLECTION SX



## SHELL COLORS\*



## CABINET COLORS\*



## COVER COLORS



## LEGENDARY MASSAGE

### 18 Personalized-Control Jets

- 1 Moto-Massage® jet
- 1 XL Rotary Hydromassage jet
- 16 Directional Precision® jets

## EASY WATER CARE

**Water Care System** FreshWater® Salt System Ready

**Filtration System** 30 sq. ft., top loading

## LEADING ENERGY EFFICIENCY

**Jet Pump** Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque

**Circulation Pump** SilentFlo® 5000 Quiet Continuous Filtration

**Heater** No-Fault® 1,000 W / 115 V or 4,000 W / 230 V

**Insulation** FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

**Cover** WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

## SIZE

**Dimensions** 6' x 6'5" x 33" / 183 cm x 196 cm x 84 cm

## CAPACITY

**Seating Capacity** 3 seats

**Water Capacity** 230 gallons / 870 liters

**Weight** 645 lbs. / 295 kg dry; 3,090 lbs. / 1,400 kg filled\*\*

## ADDITIONAL FEATURES

**Smart Spa Technology\*** Hot Spring Spas App Powered by the Connected Spa Kit

**Cover Lifters\*** CoverCradle®, CoverCradle II, or Lift 'N Glide®

**Steps\*** Hot Spot Collection Step (Almond, Havana, and Storm)

**Control System** IQ 2020® with LCD control panel  
115 V / 20 amp,\* 60 Hz (Includes GFCI protected power cord)  
or 115 V / 30 amp\* or 230 V / 50 amp,\* 60 Hz

**Lighting System** Interior: 6 multi-color LED points of light, dimmable

*\*Optional Accessories*

\*Actual colors and products may vary from print representation. See dealer to verify.

\*\*Includes water and 7 adults weighing 175 lbs. each.

★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.