

HOT SPOT® COLLECTION

STRIDE®



FreshWater®
Salt System
Ready



FiberCor®
High-Density Insulation



Exterior Lighting



*Shown with Alpine White Shell
and Almond Cabinet.*



People

3 Seats

Seating

Lounge

Jets

20 Jets

Voltage

115 V or 230 V

Size

7' x 5'5" x 29" | 213 cm x 165 cm x 74 cm

Water Care


FreshWater® Salt System Ready

HOT SPOT® COLLECTION

STRIDE®



SHELL COLORS*



CABINET COLORS*



COVER COLORS



LEGENDARY MASSAGE

20 Personalized-Control Jets

- 1 XL Directional Hydromassage jet
- 1 XL Rotary Hydromassage jet
- 3 Directional Hydromassage jets
- 1 Rotary Hydromassage jet
- 14 Directional Precision® jets

EASY WATER CARE

Water Care System FreshWater® Salt System Ready

Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque

Circulation Pump SilentFlo® 5000 Quiet Continuous Filtration

Heater No-Fault® 1,000 W / 115 V or 4,000 W / 230 V

Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

Cover WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions 7' x 5'5" x 29" / 213 cm x 165 cm x 74 cm

CAPACITY

Seating Capacity 3 seats

Water Capacity 225 gallons / 850 liters

Weight 570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology* Hot Spring Spas App Powered by the Connected Spa Kit

Cover Lifters* CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps* Hot Spot Collection Step (Almond, Havana, and Storm)

Control System IQ 2020® with LCD control panel
115 V / 20 amp,*60 Hz (Includes GFCI protected power cord)
or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz

Lighting System Interior: 6 multi-color LED points of light
Exterior: 4 multi-color LED points of light

**Optional Accessories*

*Actual colors and products may vary from print representation. See dealer to verify.

**Includes water and 7 adults weighing 175 lbs. each.

★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.