

HOT SPOT® COLLECTION

TX



FreshWater®
Salt System
Ready



FiberCor®
High-Density Insulation



Moto-Massage®



*Shown with Alpine White Shell
and Havana Cabinet.*

People	Seating	Jets	Voltage
2 Seats	Open	11 Jets	115 V or 230 V

Size
6' x 6' x 29" | 183 cm x 183 cm x 74 cm

Water Care
FreshWater® Salt System Ready

HOT SPOT® COLLECTION



TX



SHELL COLORS*



CABINET COLORS*



COVER COLORS



LEGENDARY MASSAGE

11 Personalized-Control Jets

- 1 Moto-Massage® jet
- 1 Directional Hydromassage jet
- 1 Rotary Hydromassage jet
- 8 Directional Precision® jets

EASY WATER CARE

Water Care System FreshWater® Salt System Ready

Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 4200; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque

Circulation Pump SilentFlo® 5000 Quiet Continuous Filtration

Heater No-Fault® 1,000 W / 115 V or 4,000 W / 230 V

Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

Cover WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions 6' x 6' x 29" / 183 cm x 183 cm x 74 cm

CAPACITY

Seating Capacity 2 seats

Water Capacity 190 gallons / 720 liters

Weight 635 lbs. / 290 kg dry; 2,570 lbs. / 1,165 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology* Hot Spring Spas App Powered by the Connected Spa Kit

Cover Lifters* Lift 'N Glide®

Steps* Hot Spot Collection Step (Almond, Havana, and Storm)

Control System IQ 2020® with LCD control panel
115 V / 15 amp,* 60 Hz (Includes GFCI protected power cord)
or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz

Lighting System Interior: 4 multi-color LED points of light, dimmable

**Optional Accessories*

*Actual colors and products may vary from print representation. See dealer to verify.

**Includes water and 7 adults weighing 175 lbs. each.

★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.